

# **STEELE FIRE APPARATUS**

**Haskell Texas**

**1-800-687-7639**



1/28/11

## **Proposal For Uncertain VFD**

Steele Fire Apparatus appreciates the opportunity to offer this proposal. We are very interested in meeting your needs and requirements for this Skid unit. Below are the specifications we offer in this proposal.

### **Pump**

The pump will be a Hale HPX200-H20 Pump Supplying the Stainless Steel discharge plumbing manifold. The motor driving the pump will be a 20hp Honda.

The fuel to the pump will come from a separate fuel tank made for the pump.

This manifold will supply the following discharges.

- 1-1" to the hose reel
- 1-1 ½" discharge to the rear of the bed.
- 2-1" to the 8' long whip lines with quarter turn brass ball valves
- 1-2 ½" discharge to the rear of the bed.
- 1-3/8" pump cooler line will be installed to flow water at all times.

All the valves will be industrial brass quarter turn ball valves made by Boston Metal Products.

There will be a 2 ½" Female connection at the rear of the truck for drafting and this connection will double as a tank fill from a hydrant.

Pump control panel will be mounted at the rear of the truck in the pump area.

The control panel will have a start switch, oil pressure light, throttle, choke and a 400psi discharge pressure gage.

### **Water tank**

A 500 gallon water tank and 15 gallons of foam made by Plas-Mac will be installed on the truck.

The tank will be made of ½" poly and will be baffled to meet NFPA standards.

# **STEELE FIRE APPARATUS**

## **Haskell Texas**

**1-800-687-7639**



The tank will carry a lifetime warranty.

There will be a 10" water fill with vent and over flow on top of the tank

A 10" foam fill will be on top of the foam tank.

There will be a pump platform on the rear of the tank for the pump and hose reel to mount on.

### **Nozzles**

There will be three Viper SG1560 nozzles with Pistol grip

They are adjustable from 15, 30, 50, 60 gallons per minute.

### **Foam System**

A Hale 2.1 Foam system will be installed to allow foam to all discharges.  
This foam system will allow foam to all discharges and will flow up to 1% of class A foam

### **Hose Reels**

There will be one Hannay #EF4038-17-18 hose reel mounted above the pump at the rear of the truck.

This hose reel will be an electric.

The hose reel will have 100' of 1" booster hose rated at 800 psi

# STEELE FIRE APPARATUS

**Haskell Texas**

**1-800-687-7639**



## **Delivery**

Delivery will be made approximately 30 days after receipt of the tank and equipment in our shop.

**Terms of payment are NET ON DELIVERY, unless otherwise stated.**

Due to the daily rise of cost in materials this proposal shall expire unless accepted within 25 days after the date set above. This expiration date may be extended, in writing, at the discretion of Steele Fire Apparatus.

**STEELE FIRE APPARATUS**

By: \_\_\_\_\_

Bill Steele

**STEELE FIRE APPARATUS**  
**806 NORTH FIRST STREET EAST**  
**HASKELL, TEXAS 79521**  
**1-800-687-7639**

Signatures: Bill Steele

Fire Chief or authorized Representative:

Bill Steele or authorized Representative:

*Bill Steele*